## **EXHIBIT 4. PROPOSED ARCHITECTURAL SFR STANDARDS**

## **EXHIBIT D-2**

## ARCHITECTURAL AND LANDSCAPING STANDARDS (AREA E – SINGLE-FAMILY DETACHED)

- 1. The minimum square footage for each home shall be 1,400 square feet.
- 2. The primary architectural plane of each building shall have a minimum of two (2) projections or setbacks.
- 3. The rear architectural plane of each building shall have a minimum of one (1) projections or setbacks.
  - a. Chimneys shall extend fully from grade above the eaves, be constructed of masonry or stucco material, and extend outward a minimum of 18 inches from the architectural plane to which it is attached in order to qualify as a projection or setback.
- 4. There shall be a minimum of two (2) windows per architectural plane, except for the garage side architectural plane of a single story home, and a minimum of twelve (12) windows for each home.
  - a. To qualify under this requirement each window must be a minimum of eight (8) square feet, however, one (1) ox-eye or round window measuring a minimum of 2.5 feet in diameter may be substituted. The substitution may occur only once per building.
  - b. Trim is required for all windows surrounded by masonry and may include decorative shutters, window heads, surrounds or applied trim being a minimum of 1"x4".
- 5. Entryways shall be clearly defined, visible, and a dominant feature of the façade.
- 6. All homes shall have a minimum roof pitch of 6:12 for the main body of the roof.
- 7. All roof vents and mechanical equipment shall match or be painted to match the shingle color and shall be hidden from the street view, if possible.
- 8. All homes shall have minimum roof overhangs of 12".
- 9. Each home shall have dimensional or architectural grade singles. Standard 3-tab shingles are prohibited.
- 10. Shed type or bump-out chimneys are prohibited.
- 11. 50% of the front architectural plane of each home shall be masonry excluding doors and windows and areas above a roof. Other permitted materials include cementious siding, stucco, wood, and vinyl siding having a minimum gauge of .046" and minimum of ½" lip and be certified by the Vinyl Siding Institute. Aluminum siding is prohibited. The home shall contain a minimum of two (2) distinct colors.
- 12. No two homes using the same floor plan and elevation are permitted to be located adjacent to or across the street from each other.
- 13. The maximum size allowed for a garage door shall be 9' x 16'. Garages bays shall be offset from each other a minimum of 2 feet. All dwelling units shall have an attached 2-car garage.
- 14. Front loading garage doors shall not exceed 50% of the total front architectural plane width.
- 15. Landscaping
  - a. Front yard landscaping Minimum of two (2) trees and ten (10) shrubs. Shrubs must be a minimum of 24" in height at time of planting.
  - b. Side yard landscaping Minimum 2' wide landscape bed extending 12' from the front corner break and containing a minimum of 4 shrubs.
  - c. Rear yard landscaping Minimum of one (1) tree