		ARB-00	98-2020 REV	IEW MATRIX - HAVENW	OOD		
ARCHITECTURAL FEATURE		HAVENWOOD	DRAKE				
			Α	В	С	D	E
Floor Area/Dwelling Unit (Minimum)	19.5	2200; 2,800 (Lots 93-102)	3,053	3,021	2,987	3,010	3,024
Corner Breaks; Front (Minimum)	Two-Story Structures	3	3	3	3	3	3
Corner Breaks; Left Side (Minimum)	Two-Story Structures	2	2	2	2	2	2
Corner Breaks; Right Side (Minimum)	Two-Story Structures	2	2	2	2	3	3
Corner Breaks; Rear (Minimum)	Two-Story Structures	2	2	2	2	2	2
Porch Size (Minimum; sq. ft.)		16	43	102	100	100	95
Masonry Percentage (Minimum)	Primary Architectural Plane	50%	6%	(20.3%), (27.5%)	(5.8%) , (20%)	(8.5%), (23.7%)	(10.6%), (2
Material Restrictions	Vinyl (.048" minimum)	NO	NO	NO	NO	NO	NO
	Aluminum	NO	NO	NO	NO	NO	NO
Roof Pitch (Minimum)	Primary Ridge	6/12	10/12	6/12	6/12	8/12	12/12
Roof Ridgelines (Minimum)	Two-Story Structures	3	2	4	3	3	4
Roof Overhang; From Framing (Minimum; in.)		12	12	12	12	12	12
Number of Windows; Front (Minimum)	Two-Story Structures	4	9	4	9	9	7
Number of Windows; Left Side (Minimum)	Two-Story Structures	3	1	1	1	1	2
Number of Windows; Right Side (Minimum)	Two-Story Structures	3	3	3	3	3	3
Number of Windows; Rear (Minimum) Number of Windows; 1 otal Aggregate (Minimum)	Two-Story Structures	3	8	9	7	8	8
	Two-Story Structures	16	21	17	20	21	20
Window Treatment Required	Primary Architectural Plane	YES	YES	YES	YES	YES	YES
	Secondary Architectural Plane	NO	NO	NO	NO	NO	NO
Garage Door Percentage (Maximum)	Two-Story Structures	20%	18%	20%	17%	18%	17%

Garage door % calculated by OP

EXHIBIT 5

	NOTES
24	
and a barrangement and statistic orthogonation of and	
(21.6%)	
)	
)	
12	
S D	
%	