


Board of Public Works and Safety Agenda Item

Cover Sheet

MEETING DATE: July 23, 2024
☐ Consent Agenda Item
☐ Previously Discussed Item
☐ Miscellaneous
ITEM #: <u>7</u>
INITIATED BY: James Alexander
☐ Bring Paperwork from Previous Meeting
□ Verbal
☐ No Paperwork at Time of Packets



TO: Board of Public Works

FROM: James Alexander, Street Dept. Fleet Manager

CC: Lindsay Downing

SUBJECT: Shop Service Truck

DATE: July 23, 2024

The purpose of this memo is to request approval to replace the Street Department shop service truck.

Background


The department needs to replace its existing service truck due to age and condition.

Proposed Purchase

We have obtained three quotes for a new service truck and the trade in value for our outgoing vehicle. The quote from Don Hinds is for a complete package. The quotes from Reading Trucks and from Mid-State Equipment are for service bodies only. The chassis would then be purchased separately. The best quote that met our specifications was from Don Hinds Ford, with a final cost of \$105,562. This purchase is part of our 2024 budget, and we have a purchase order from OFA that is attached to this request.

It is my recommendation to purchase a new shop service truck from Don Hinds Ford as part of the 2024 Street Department annual budget.





2024 Shop Service Truck Replacement

Don Hinds Ford

MSRP Complete: \$120,561.50

Trade: \$15,000 Cost: \$105,562

Reading Trucks

Service body only: \$85,832 Truck Chassis: \$57,671.50

Cost: \$143,503.50

Mid-State Trucks

Service body only: \$53,844 Truck Chassis: \$57,671.50

Cost: \$111,515.50



F550 Supercab with service body, Vanair compressor and lift gate



Prepared by: Todd Gilkey

03/22/2024 Don Hinds Ford Inc | 12610 Ford Drive Fishers Indiana | 460382892

2024 F-550 Chassis 4x4 SD Super Cab 192" WB DRW XL (X5H)

Price Level: 425 | Quote ID: NoblF550-S REVISED 3-22-24 to add VANAIR welder/compressor

As Configured Vehicle

Code Description MSRP

Base Vehicle

X5H Base Vehicle Price (X5H) \$59,305.00

Packages

Order Code 660A N/C

Includes:

- Engine: 7.3L 2V DEVCT NA PFI V8 Gas
- Transmission: TorqShift 10-Speed Automatic

10R140 with neutral idle. Includes SelectShift and selectable drive modes: normal, tow/haul, eco, slippery roads and off-road.

- GVWR: 18,000 lbs Payload Package
- Tires: 225/70Rx19.5G BSW A/P
- Wheels: 19.5" x 6" Argent Painted Steel Hub covers/center ornaments not included.
- Radio: AM/FM Stereo w/MP3 Player

Includes 6 speakers.

- SYNC 4 Communications & Entertainment System

Includes enhanced voice recognition, 911 Assist, 8" LCD center stack screen, AppLink, 1 smart-charging USB port and trailer brake controller.

Powertrain

99N Engine: 7.3L 2V DEVCT NA PFI V8 Included

Gas

44G Transmission: TorqShift 10-Speed Included

Automatic

10R140 with neutral idle. Includes SelectShift and selectable drive modes: normal, tow/haul, eco,

slippery roads and off-road.

X8L Limited Slip w/4.88 Axle Ratio \$395.00

STDGV GVWR: 18,000 lbs Payload Package Included

Wheels & Tires

TGJ Tires: 225/70Rx19.5G BSW A/P Included

Wheels: 19.5" x 6" Argent Painted Included

Steel

Hub covers/center ornaments not included.

512 Spare Tire & Wheel \$350.00

Required in Rhode Island.

Excludes carrier.

Includes:

Prices and content availability as shown are subject to change and should be treated as estimates only. Actual base vehicle, package and option pricing may vary from this estimate because of special local pricing, availability or pricing adjustments not reflected in the dealer's computer system. See salesperson for the most current information.

1



03/22/2024

Don Hinds Ford Inc | 12610 Ford Drive Fishers Indiana | 460382892

2024 F-550 Chassis 4x4 SD Super Cab 192" WB DRW XL (X5H)

Price Level: 425 | Quote ID: NoblF550-S

As	Configured	Vehicle ((cont'd)	
, ,	Gornigaroa	V 0111010		,

Code Description MSRP

- 6-Ton Hydraulic Jack

Seats & Seat Trim

1 Cloth 40/20/40 Split Bench Seat \$100.00

Includes center armrest, cupholder, storage and driver's side manual lumbar.

Other Options

PAINT Monotone Paint Application STD

192WB 192" Wheelbase STD

STDRD Radio: AM/FM Stereo w/MP3 Player Included

Includes 6 speakers.

Includes:

- SYNC 4 Communications & Entertainment System

Includes enhanced voice recognition, 911 Assist, 8" LCD center stack screen, AppLink, 1 smart-

charging USB port and trailer brake controller.

473 Snow Plow Prep Package \$250.00

Includes pre-selected springs (see order guide supplemental reference for springs/FGAWR of specific vehicle configurations). Note 1: Restrictions apply; see supplemental reference or body builders layout book for details. Note 2: Also allows for the attachment of a winch. Note 3: Highly recommended to add (86M) dual battery on 7.3L gas engine. Adding (67B) 410 amp dual

alternators for diesel engine is highly recommended for max power output.

61J 6-Ton Hydraulic Jack Included

86M Dual 68 AH/65 AGM Battery N/C

67B 410 Amp Dual Alternators \$115.00

Includes 250 Amp + 160 Amp.

18B Platform Running Boards \$445.00

59H Center High-Mounted Stop Lamp N/C

(CHMSL)

153 Front License Plate Bracket N/C

Standard in states requiring 2 license plates and optional to all others.

Rear View Camera & Prep Kit \$415.00

Pre-installed content includes cab wiring and frame wiring to the rear most cross member. Upfitters kit includes camera with mounting bracket, 20' jumper wire and camera mounting/aiming

kit includes camera with mounting bracket, 20° jumper wire and camera mounting/aiming instructions.

IIISIIUCIIOIIS

43C 110V/400W Outlet \$175.00

Includes 1 in-dash mounted outlet.

76C Exterior Backup Alarm (Pre-Installed) \$175.00



03/22/2024

Don Hinds Ford Inc | 12610 Ford Drive Fishers Indiana | 460382892

2024 F-550 Chassis 4x4 SD Super Cab 192" WB DRW XL (X5H)

Price Level: 425 | Quote ID: NoblF550-S

As	Configured	l Vehicle	(cont'd)	
			()	,

Code	Description	MSRP
79V	COV Required	N/A
C09	Priced DORA	N/C

Dealer Installed Options

AHQAB First Aid Kit w/Ford Logo \$50.00

Shipped separately from the vehicle for dealer installation.

Fleet Options

WARANT Fleet Customer Powertrain Limited
Warranty

Requires valid FIN code.

Ford is increasing the 5-year 60,000-mile limited powertrain warranty to 5-years, 100,000 miles. Only Fleet purchasers with a valid Fleet Identification Number (FIN code) will receive the extended warranty. When the sale is entered into the sales reporting system with a sales type fleet along with a valid FIN code, the warranty extension will automatically be added to the vehicle. The extension will stay with the vehicle even if it is subsequently sold to a non-fleet customer before the expiration. This extension applies to both gas and diesel powertrains. Dealers can check for the warranty extension on eligible fleet vehicles in OASIS. Please refer to the Warranty and Policy Manual section 3.13.00 Gas Engine Commercial Warranty. This change will also be reflected in the printed Warranty Guided distributed with the purchase of every new vehicle.

Emissions

425 50-State Emissions System STD

Exterior Color

Z1 01 Oxford White

Interior Color

1S_06 Medium Dark Slate w/Cloth 40/20/40 N/C

Split Bench Seat

Upfit Options

6132D54* 6132D54 11' Knapheide Service Body \$62,890.00



03/22/2024

2024 F-550 Chassis 4x4 SD Super Cab 192" WB DRW XL (X5H)

Price Level: 425 | Quote ID: NoblF550-S

As Configured Vehicle (cont'd) Code **Description**

MSRP

- Knapheide model 6132D54. 11ft Service Body DRW Chassis 132.25" long x 40" high with 20" deep compartments 54" wide floor / 94" wide overall

- Premium "slammable" tailgate with center release
 LED surface mount lights with automotive wire harness
- Rotary latches on compartment doors, w/automotive seals
- Body fully undercoated

- Finish paint white to match the cab
 14 gauge two-sided A-40 galvaneal steel body shell
 All stainless steel continuous door hinges
 (4) Cargo tie down rings in bed floor. 2 at rear / 2 mid-bed
- (2) Chrome plated zinc alloy grab handles @ rear of body. Spare tire holder mounted to load area side wall, at rear.
- Knapheide Gas bottle drop well with tank holder and J-hooks. ((Curbside front compartment of body)- ** Ti (both sides). Treadplate steel installed top of side compartments,
- 6 year limited warranty on body
- REAR STROBES IN FACTORY LED LIGHTS (AMBER) SURFACE MOUNTED STROBES ON FRONT GRILL (WHITE/AMBER).
- (1) 24" MODULAR LIGHT BAR. (3) AMBER & (3) CLEAR STROBES
 - MOUNTED ON CAB GUARD
- (4) 5" LED ARTICULATING WORK LIGHTS
- 4500 LUMENS EACH
- BUILT IN SWITCH
- ROTATING BASE & LENSES
- SPRAY LINE BED FLOOR, SIDE WALLS, BULKHEAD, BOX TOPS & INSIDE OF TAILGATE

VANAIR AIR-N-ARC 300 H SYSTEM

- FULLY CONTAINED SYSTEM
 ROTARY SCREW AIR COMPRESSOR
 40 CFM / 175 PSI MAX PRESSURE
 7KW PEAK GENERATOR / 6.8KW CONTINUOUS
 - AC POWER SINGLE PHASE
- 12V AND 240V OUTLETS
- DC WELDER
 270 AMP AT FUUL DUTY CYCLE BATTERY 300AMP CHARGER/BOOSTER
- PANEL HARNESS
- 1/0 TWIST WELDER CABLES (50 FT CABLES)
- 2/0 BATTERY/BOOSTER CABLES 25 FT)
- PM KIT FOR COMPRESSOR
- MOUNTED ON STREET SIDE
- 1/2" X 50' HOSE REEL MOUNTED, CURB SIDE TOP OF COMPARTMENTS

(1) CTECH DRAWER UNIT

- (3) 3" DEEP DRAWERS (2) -5" DEEP DRAWERS (1) 7" DEEP DRAWER

- MOUNTED IN CURB SIDE REAR VERTICAL COMPARTMENT

(1) CTECH DRAWER UNIT

- (2) 3" DRAWERS MOUNTED IN CURB SIDE HORIZONTAL COMPARTMENT

(1) SET OF DUAL 50 GALLON TANKS IN LOAD AREA

- MOUNTED IN BED, IN FRONT OF BULKHEAD 50 GALLONS FUEL & 50 GALLONS OIL FUEL HOSE ON REEL (50 FT X 1 INCH HOSE) OIL HOSE ON REEL (50 FT X 1/2 INCH HOSE) HOSE REELS MOUNTED ON CURB SIDE, TOP
- TOMMYGATE MODEL G2-54-1342 FOR SVC BODY
- 1,300 LBS CAPACITY
- 42" TRAVEL
- STEEL TREADPLATE PLATFORM, (49" X27") W/ 6" TAPER
- FULLY ENCLOSED HYDRAULIC SYSTEM, WITH RECESSED CONTROLS



03/22/2024

Don Hinds Ford Inc | 12610 Ford Drive Fishers Indiana | 460382892

2024 F-550 Chassis 4x4 SD Super Cab 192" WB DRW XL (X5H)

Price Level: 425 | Quote ID: NoblF550-S

As Configure	ed Vehicle	(cont'd)
7 10 00111190111	0 00.0	(0 0 0.)

As Configured Veri		
Code	Description	MSRP
SUBTOTAL		\$124,665.00
Destination Charge		\$1,995.00
TOTAL		\$126,660.00



03/22/2024

Don Hinds Ford Inc | 12610 Ford Drive Fishers Indiana | 460382892

2024 F-550 Chassis 4x4 SD Super Cab 192" WB DRW XL (X5H)

Price Level: 425 | Quote ID: NoblF550-S

Pricing Summary - Single Vehicle

	MSRP
Vehicle Pricing	
Base Vehicle Price	\$59,305.00
Options	\$2,470.00
Colors	\$0.00
Upfitting	\$62,890.00
Fleet Discount	\$0.00
Fuel Charge	\$0.00
Destination Charge	\$1,995.00
Subtotal	\$126,660.00

Pre-Tax Adjustments

Code	Description	MSRP
Dealer Discount	Dealer's discount	-\$5,500.00
Government	Indiana Gov't price Concession	-\$600.00
Subtotal		\$120,560.00

Post-Tax Adjustments

Code	Description	MSRP
Tire Tax	State Tire Tax	\$1.50
Subtotal		\$120,561.50
Total		\$120,561.50

Customer Signature Acceptance Date

Possible Trades: (not included in pricing above)

- 2010 F550 with service body. Vin ending EA21753. 28645 miles. \$15,000.00
 2014 F550 with alum flatbed. Vin ending EB67304. 28832 miles. \$17,000.00
 2016 F550 with alum flatbed. Vin ending EB67489. 29426 miles \$17,000.00

Prices and content availability as shown are subject to change and should be treated as estimates only. Actual base vehicle, package and option pricing may vary from this estimate because of special local pricing, availability or pricing adjustments not reflected in the dealer's computer system. See salesperson for the most current information.

6

^{**} These trade values are good for 30 days. Good thru 4/22/23



03/22/2024

Don Hinds Ford Inc | 12610 Ford Drive Fishers Indiana | 460382892

2024 F-550 Chassis 4x4 SD Super Cab 192" WB DRW XL (X5H)

Price Level: 425 | Quote ID: NoblF550-S

Warranty

Standard Warranty

Basic Warranty	
Basic warranty	36 months/36,000 miles
Powertrain Warranty	
Powertrain warranty	60 months/60,000 miles
Corrosion Perforation	
Corrosion perforation warranty	60 months/unlimited
Roadside Assistance Warranty	
Roadside warranty	60 months/60,000 miles



03/07/2024

Don Hinds Ford Inc | 12610 Ford Drive Fishers Indiana | 460382892

2024 F-550 Chassis 4x4 SD Super Cab 192" WB DRW XL (X5H)

Price Level: 425 | Quote ID: NoblF550

As Configured Vehicle

Code Description MSRP

Base Vehicle

X5H Base Vehicle Price (X5H) \$59,305.00

Packages

Order Code 660A N/C

Includes:

- Engine: 7.3L 2V DEVCT NA PFI V8 Gas
- Transmission: TorqShift 10-Speed Automatic

10R140 with neutral idle. Includes SelectShift and selectable drive modes: normal, tow/haul, eco, slippery roads and off-road.

- GVWR: 18,000 lbs Payload Package
- Tires: 225/70Rx19.5G BSW A/P
- Wheels: 19.5" x 6" Argent Painted Steel Hub covers/center ornaments not included.
- Radio: AM/FM Stereo w/MP3 Player

Includes 6 speakers.

- SYNC 4 Communications & Entertainment System

Includes enhanced voice recognition, 911 Assist, 8" LCD center stack screen, AppLink, 1 smart-charging USB port and trailer brake controller.

Powertrain

99N Engine: 7.3L 2V DEVCT NA PFI V8 Included

Gas

44G Transmission: TorqShift 10-Speed Included

Automatic

10R140 with neutral idle. Includes SelectShift and selectable drive modes: normal, tow/haul, eco,

slippery roads and off-road.

X8L Limited Slip w/4.88 Axle Ratio \$395.00

STDGV GVWR: 18,000 lbs Payload Package Included

Wheels & Tires

TGJ Tires: 225/70Rx19.5G BSW A/P Included

Wheels: 19.5" x 6" Argent Painted Included

Steel

Hub covers/center ornaments not included.

512 Spare Tire & Wheel \$350.00

Required in Rhode Island.

Excludes carrier.

Includes:



03/07/2024

Don Hinds Ford Inc | 12610 Ford Drive Fishers Indiana | 460382892

2024 F-550 Chassis 4x4 SD Super Cab 192" WB DRW XL (X5H)

Price Level: 425 | Quote ID: NoblF550

As	Configured	Vehicle ((cont'd)	
			(00.110.)	

Code Description MSRP

- 6-Ton Hydraulic Jack

Seats & Seat Trim

1 Cloth 40/20/40 Split Bench Seat \$100.00

Includes center armrest, cupholder, storage and driver's side manual lumbar.

Other Options

PAINT Monotone Paint Application STD

192WB 192" Wheelbase STD

STDRD Radio: AM/FM Stereo w/MP3 Player Included

Includes 6 speakers.

Includes:

- SYNC 4 Communications & Entertainment System

Includes enhanced voice recognition, 911 Assist, 8" LCD center stack screen, AppLink, 1 smart-

charging USB port and trailer brake controller.

473 Snow Plow Prep Package \$250.00

Includes pre-selected springs (see order guide supplemental reference for springs/FGAWR of specific vehicle configurations). Note 1: Restrictions apply; see supplemental reference or body builders layout book for details. Note 2: Also allows for the attachment of a winch. Note 3: Highly recommended to add (86M) dual battery on 7.3L gas engine. Adding (67B) 410 amp dual

alternators for diesel engine is highly recommended for max power output.

61J 6-Ton Hydraulic Jack Included

86M Dual 68 AH/65 AGM Battery N/C

67B 410 Amp Dual Alternators \$115.00

Includes 250 Amp + 160 Amp.

18B Platform Running Boards \$445.00

59H Center High-Mounted Stop Lamp N/C

(CHMSL)

153 Front License Plate Bracket N/C

Standard in states requiring 2 license plates and optional to all others.

Rear View Camera & Prep Kit \$415.00

Pre-installed content includes cab wiring and frame wiring to the rear most cross member. Upfitters

kit includes camera with mounting bracket, 20' jumper wire and camera mounting/aiming instructions.

II ISU UCUONS.

43C 110V/400W Outlet \$175.00

Includes 1 in-dash mounted outlet.

76C Exterior Backup Alarm (Pre-Installed) \$175.00



03/07/2024

Don Hinds Ford Inc | 12610 Ford Drive Fishers Indiana | 460382892

2024 F-550 Chassis 4x4 SD Super Cab 192" WB DRW XL (X5H)

Price Level: 425 | Quote ID: NoblF550

As Configured \	ehicle ((cont'd)
-----------------	----------	----------

Code	Description	MSRP
79V	COV Required	N/A
C09	Priced DORA	N/C

Dealer Installed Options

AHQAB First Aid Kit w/Ford Logo \$50.00

Shipped separately from the vehicle for dealer installation.

Fleet Options

WARANT Fleet Customer Powertrain Limited N/C
Warranty

Requires valid FIN code.

Ford is increasing the 5-year 60,000-mile limited powertrain warranty to 5-years, 100,000 miles. Only Fleet purchasers with a valid Fleet Identification Number (FIN code) will receive the extended warranty. When the sale is entered into the sales reporting system with a sales type fleet along with a valid FIN code, the warranty extension will automatically be added to the vehicle. The extension will stay with the vehicle even if it is subsequently sold to a non-fleet customer before the expiration. This extension applies to both gas and diesel powertrains. Dealers can check for the warranty extension on eligible fleet vehicles in OASIS. Please refer to the Warranty and Policy Manual section 3.13.00 Gas Engine Commercial Warranty. This change will also be reflected in the printed Warranty Guided distributed with the purchase of every new vehicle.

Emissions

425 50-State Emissions System STD

Exterior Color

Z1 01 Oxford White

Interior Color

1S_06 Medium Dark Slate w/Cloth 40/20/40 N/C
Split Bench Seat

SUBTOTAL \$61,775.00

Destination Charge \$1,995.00

TOTAL \$63,770.00



03/07/2024

Don Hinds Ford Inc | 12610 Ford Drive Fishers Indiana | 460382892

2024 F-550 Chassis 4x4 SD Super Cab 192" WB DRW XL (X5H)

Price Level: 425 | Quote ID: NoblF550

Pricing Summary - Single Vehicle

		MSRP
Vehicle Pricing		
Base Vehicle Price		\$59,305.00
Options		\$2,470.00
Colors		\$0.00
Upfitting		\$0.00
Fleet Discount		\$0.00
Fuel Charge		\$0.00
Destination Charge		\$1,995.00
Subtotal		\$63,770.00
Pre-Tax Adjustmen	its	
Code	Description	MSRP
Government	Indiana Gov't price Concession	-\$600.00
Dealer Discount	Dealer's discount	-\$5,500.00
Subtotal		\$57,670.00
Post-Tax Adjustme	nts	
Code	Description	MSRP
Tire Tax	State Tire Tax	\$1.50
Subtotal		\$57,671.50
Total		\$57,671.50
Customer Signature		Acceptance Date



03/07/2024

Don Hinds Ford Inc | 12610 Ford Drive Fishers Indiana | 460382892

2024 F-550 Chassis 4x4 SD Super Cab 192" WB DRW XL (X5H)

Price Level: 425 | Quote ID: NoblF550

Warranty

Standard Warranty

Basic Warranty	
Basic warranty	36 months/36,000 miles
Powertrain Warranty	
Powertrain warranty	60 months/60,000 miles
Corrosion Perforation	
Corrosion perforation warranty	60 months/unlimited
Roadside Assistance Warranty	
Roadside warranty	60 months/60.000 miles

P 800-540-4479 317-849-4903



Quotation		
Date	Quotation #	
2/1/2024	6337	

Name / Address	Ship To		
NOBLESVILLE STREET DEPARTMENT 1575 PLEASANT STREET NOBLESVILLE IN 46060	James Alexa	nder	
3% HANDLING FEE FOR ALL C/C	REP ID	TERMS	GOOD THRU
TRANSACTIONS	JK	NET 25 Days	3-1-24

Qty	Item	Description	Rate	Total
1	EQUIP.	11' Duramag S-Series Aluminum service body40" compartment heightGas bottle storage front curb side compartmentCompartment lightingSingle shelf in compartmentsPowder coat RED	20,500.00	20,500.00
1	EQUIP.	MAGNUM ALUMINUM FRONT BULKHEADPowder coat black	999.00	999.00

Subtotal	
Sales Tax (7.0%)	
Total	

P 800-540-4479 317-849-4903



Quotation		
Date	Quotation #	
2/1/2024	6337	

Name / Address	Ship To
NOBLESVILLE STREET DEPARTMENT 1575 PLEASANT STREET NOBLESVILLE IN 46060	James Alexander

3% HANDLING FEE FOR ALL C/C TRANSACTIONS

REP ID	TERMS	GOOD THRU
JK	NET 25 Days	3-1-24

Qty	Item	Description	Rate	Total
1	EQUIP.	VANAIR AIR-NARC 300H HYDRAULIC DRIVEN 19GPM@2800PSI; PUMP RATED 2900PSI MINIMUM PRESSURE RELIEF SET @ 3200PSI OPEN CENTER HYD SYS 300 AMP DC CC/CV WELDER 6.8KW GENERATOR 40 CFM ROTARY SCREW COMPRESSOR 12V/24V BATTERY CHARGE/BOOST INTEGRATED HYDRAULIC COOLER REMOTE MNT CAPABLE CNTRL PANEL WELD & JUMP LEADS NOT INCLUDED CONNECT HARNESS NOT NEEDED IF MOUNTING PANEL ON MACHINE 12VDC COLD WEATHER HEATERS	15,310.00	15,310.00
1	PARTS1	Hydraulic components to opperate vanair systemPTO and PUMP off of transmissionFront bulkhead mount oil reserviorAll hoses and fittings	4,500.00	4,500.00

Subtotal	
Sales Tax (7.0%)	
Total	

P 800-540-4479 317-849-4903



Quotation		
Date	Quotation #	
2/1/2024	6337	

Name / Address	Ship To
NOBLESVILLE STREET DEPARTMENT	James Alexander
1575 PLEASANT STREET	
NOBLESVILLE IN 46060	

3% HANDLING FEE FOR ALL C/C TRANSACTIONS

REP ID	TERMS	GOOD THRU
JK	NET 25 Days	3-1-24

Qty	Item	Description	Rate	Total
1	EQUIP.	MAXON C2 DUAL DRIVE LIFTGATEGalvanized frameAluminum 49X27 platform1300 LB capacity	2,950.00	2,950.00
1	1801052L	HITCH, UNIV FIT SERV BODY W/44in CROSS TUBE, 2.5in RCVR TUBE; CLASS 5, LONG BRACKETS	350.00	350.00
1	TC1007P	7-WAY TRUCK SIDE	10.00	10.00
1	EQUIP.	100 gallon HD treadplate aluminum transfer tankDriver side fill	1,000.00	1,000.00
1	EQUIP.	50 gallon HD treadplate aluminum transfer tankDriver side fill	875.00	875.00
1	FR1210HA1	FILL RITE 12V ELECTRIC TRANSFER PUMP; 15 GPM; AUTOMATIC SHUT OFF; DIESEL	575.00	575.00
1	FR410B	Liquid Transfer Tank Pump; Used To Transfer Diesel/Oil/Water; Diaphragm Pump; 1/4 HP Motor Operated; Glass-Filled Polypropylene Housing; 12 Volt DC; 13 Gallon Per Minute; 15 PSI; With Telescoping Steel Suction Tube/ 1 Inch x 12 Foot Length Hose/ Manual Nozzle/ Nozzle Boot; 20 Amps	975.00	975.00
1	SHOP-001	ENVIRONMENTAL & MISC. SHOP ITEMSinc. misc steel for tire rack	175.00	175.00

Subtotal	
Sales Tax (7.0%)	
Total	

TRANSACTIONS

P 800-540-4479 317-849-4903



Quotation		
Date	Quotation #	
2/1/2024	6337	

3-1-24

Name / Address	Ship To		
NOBLESVILLE STREET DEPARTMENT 1575 PLEASANT STREET NOBLESVILLE IN 46060	James Alexander		
3% HANDLING FEE FOR ALL C/C	REP ID	TERMS	GOOD THRU

JK

NET 25 Days

Qty	Item	Description	Rate	Total
1	LABOR	install service body; hitch; bulkhead; liftgate; hydraulic components; compressor; fabricate tire rack	5,625.00	5,625.00
				I

Subtotal	\$53,844.00
Sales Tax (7.0%)	\$0.00
Total	\$53,844.00



PROPOSAL

Install on a client supplied 2024/25 Ford F-550 DRW, Super Cab, 4x4, Gas, 84" c/a.

FURNISH & INSTALL:

Reading Model MM200 Service Body with Cab Guard, LED Strip Compartment Lighting, Torch Bottle Holders (short) and Hose Hook in Front Curbside Compartment. LineX Spray-on Liner in Complete Cargo Area and Tops of Compartments. Custom Fabricated Wheel/Tire Holder mounted in Cargo Area to handle 22.5" Tires.

Weather Guard 100 Gallon Transfer Tank and Fill-Rite 12 Volt Fuel Pump. Weather Guard 50 Gallon Transfer Tank and GROZ 12 Volt Oil Pump. Both located in cargo area behind the hydraulic reservoir, and each plumbed to a 50 Hose Reel mounted atop the Curbside Compartments.

Vanair Air-n-Arc 300H Hydraulic Driven Compressor, Welder, Generator, Battery Charger/Booster Mounted on Top of Compartment Curbside Rear. Control Panel to be Located in Compartment Below. Reelcraft 50' x 1/2" Hose Reel with Roller Fairlead Thru Rear Wall and Filter/Lube/Regulator to be Located in same Curbside Rear Compartment.

Force America PTO & Pump. Hydraulic Reservoir located ahead of the Transfer Tank against front bulkhead. Hoses, Fittings and AW32 Hydraulic Fluid.

Thieman TT-15 Service Body Lift-gate with Two Piece Aluminum Platform. 1500 Lb. Capacity.

Class V, 2-1/2" Receiver Hitch and 7-Way/4-Way Trailer Plug.

(6) Hella LED Work Lights 357105012, one each at corners and mid-point of service body. Hella LED Mini Strobe Light Bar H27996001 mounted to top of cab guard. (4) Hella LED Surface Strobes H22890001 mounted (2) at rear each side of service body and (2) on front grill of truck.

Total Price Installed......\$ 85,832.00

Submitted To:

James Alexander, City of Noblesville Street Department

Submitted By:

Tim Brattain, Territory Sales Manager Reading Truck - Indianapolis

317-914-3893 tbrattain@readingtruck.com

CITY OF NOBLESVILLE STREET DEPARTMENT

2024 BID SPECIFICATIONS FOR SERVICE TRUCK

Body must be constructed of steel with stainless steel hinges and latches. Spray on bedlliner covering entire inside and top. 2 SIZE: Unit shall have a minimum 11 ft. length, 54 in. wide floor, and side height of 40 in. 3 ENGINE: Gasoline V8 engine. 4 TRANSMISSION: Full automatic shift with selectable drive modes. Minimum 10 forward speeds. 5 DRIVE AXLES: Must be selectable 4 wheel drive. Automatic locking differential in rear axle. 6 BRAKES: Service brakes shall be all hydraulic, power operated, antilock at both axles. 7 TIRES: All tires shall be a minimum of 225/70R19.5. 8 AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. 10 HYDRAULIC STORAGE: Minimum 50 gal. bulk hydraulic storage tank, mounted YES NO	1	Body Material		
steel hinges and latches. Spray on bedlliner covering entire inside and top. 2 SIZE: Unit shall have a minimum 11 ft. length, 54 in. wide floor, and side height of 40 in. 3 ENGINE: Gasoline V8 engine. 4 TRANSMISSION: Full automatic shift with selectable drive modes. Minimum 10 forward speeds. 5 DRIVE AXLES: Must be selectable 4 wheel drive. Automatic locking differential in rear axle. 6 BRAKES: Service brakes shall be all hydraulic, power operated, antilock at both axles. 7 TIRES: All tires shall be a minimum of 225/70R19.5. 8 AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. 10 LIFT GATE: Self contained hydraulic lift gate with minimum 1,200 Ibs capacity and treadplate platform.	'		VEC	NO
Spray on bedlliner covering entire inside and top. SIZE: Unit shall have a minimum 11 ft. length, 54 in. wide floor, and side height of 40 in. SINGINE: Gasoline V8 engine. TRANSMISSION: Full automatic shift with selectable drive modes. Minimum 10 forward speeds. DRIVE AXLES: Must be selectable 4 wheel drive. Automatic locking differential in rear axle. Service brakes shall be all hydraulic, power operated, antilock at both axles. TIRES: All tires shall be a minimum of 225/70R19.5. AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose compressor, 12/24 volit jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. YES NO PIFT GATE: Self contained hydraulic lift gate with minimum 1,200 Ibs capacity and treadplate platform.			TES	NO
2 SIZE: Unit shall have a minimum 11 ft. length, 54 in. wide floor, and side height of 40 in. 3 ENGINE: Gasoline V8 engine. 4 TRANSMISSION: Full automatic shift with selectable drive modes. Minimum 10 forward speeds. 5 DRIVE AXLES: Must be selectable 4 wheel drive. Automatic locking differential in rear axle. 7 TIRES: All tires shall be all hydraulic, power operated, antilock at both axles. 7 TIRES: All tires shall be equipped with a multi-purpose compressor shall be equipped with a multi-purpose compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. 10 HYDRAULIC STORAGE: Minimum 50 gal. bulk hydraulic storage tank, mounted		steel ninges and latches.		
2 SIZE: Unit shall have a minimum 11 ft. length, 54 in. wide floor, and side height of 40 in. 3 ENGINE: Gasoline V8 engine. 4 TRANSMISSION: Full automatic shift with selectable drive modes. Minimum 10 forward speeds. 5 DRIVE AXLES: Must be selectable 4 wheel drive. Automatic locking differential in rear axle. 7 TIRES: All tires shall be all hydraulic, power operated, antilock at both axles. 7 TIRES: All tires shall be equipped with a multi-purpose compressor shall be equipped with a multi-purpose compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. 10 HYDRAULIC STORAGE: Minimum 50 gal. bulk hydraulic storage tank, mounted				
Unit shall have a minimum 11 ft. length, 54 in. wide floor, and side height of 40 in. 3 ENGINE: Gasoline V8 engine. 4 TRANSMISSION: Full automatic shift with selectable drive modes. Minimum 10 forward speeds. 5 DRIVE AXLES: Must be selectable 4 wheel drive. Automatic locking differential in rear axle. 6 BRAKES: Service brakes shall be all hydraulic, power operated, antilock at both axles. 7 TIRES: All tires shall be a minimum of 225/70R19.5. 8 AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. 10 HYDRAULIC STORAGE: Minimum 50 gal. bulk hydraulic storage tank, mounted YES NO		Spray on bedlliner covering entire inside and top.	YES	NO
Unit shall have a minimum 11 ft. length, 54 in. wide floor, and side height of 40 in. 3 ENGINE: Gasoline V8 engine. 4 TRANSMISSION: Full automatic shift with selectable drive modes. Minimum 10 forward speeds. 5 DRIVE AXLES: Must be selectable 4 wheel drive. Automatic locking differential in rear axle. 6 BRAKES: Service brakes shall be all hydraulic, power operated, antilock at both axles. 7 TIRES: All tires shall be a minimum of 225/70R19.5. 8 AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. 10 HYDRAULIC STORAGE: Minimum 50 gal. bulk hydraulic storage tank, mounted YES NO				
floor, and side height of 40 in. 3 ENGINE: Gasoline V8 engine. 4 TRANSMISSION: Full automatic shift with selectable drive modes. Minimum 10 forward speeds. 5 DRIVE AXLES: Must be selectable 4 wheel drive. Automatic locking differential in rear axle. 6 BRAKES: Service brakes shall be all hydraulic, power operated, antilock at both axles. 7 TIRES: All tires shall be a minimum of 225/70R19.5. 8 AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. 10 LIFT GATE: Self contained hydraulic lift gate with minimum 1,200 Ibs capacity and treadplate platform.	2	SIZE:		
floor, and side height of 40 in. 3 ENGINE: Gasoline V8 engine. 4 TRANSMISSION: Full automatic shift with selectable drive modes. Minimum 10 forward speeds. 5 DRIVE AXLES: Must be selectable 4 wheel drive. Automatic locking differential in rear axle. 6 BRAKES: Service brakes shall be all hydraulic, power operated, antilock at both axles. 7 TIRES: All tires shall be a minimum of 225/70R19.5. 8 AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. 10 LIFT GATE: Self contained hydraulic lift gate with minimum 1,200 Ibs capacity and treadplate platform.		Unit shall have a minimum 11 ft. length, 54 in. wide	YES	NO
3 ENGINE: Gasoline V8 engine. 4 TRANSMISSION: Full automatic shift with selectable drive modes. Minimum 10 forward speeds. 5 DRIVE AXLES: Must be selectable 4 wheel drive. Automatic locking differential in rear axle. 6 BRAKES: Service brakes shall be all hydraulic, power operated, antilock at both axles. 7 TIRES: All tires shall be a minimum of 225/70R19.5. 8 AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. 9 LIFT GATE: Self contained hydraulic lift gate with minimum 1,200 YES NO Ibs capacity and treadplate platform.		_		
Gasoline V8 engine. 4 TRANSMISSION: Full automatic shift with selectable drive modes. Minimum 10 forward speeds. 5 DRIVE AXLES: Must be selectable 4 wheel drive. Automatic locking differential in rear axle. 6 BRAKES: Service brakes shall be all hydraulic, power operated, antilock at both axles. 7 TIRES: All tires shall be a minimum of 225/70R19.5. 8 AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. 10 HYDRAULIC STORAGE: Minimum 50 gal. bulk hydraulic storage tank, mounted YES NO		, , , , , , , , , , , , , , , , , , ,		
Gasoline V8 engine. 4 TRANSMISSION: Full automatic shift with selectable drive modes. Minimum 10 forward speeds. 5 DRIVE AXLES: Must be selectable 4 wheel drive. Automatic locking differential in rear axle. 6 BRAKES: Service brakes shall be all hydraulic, power operated, antilock at both axles. 7 TIRES: All tires shall be a minimum of 225/70R19.5. 8 AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. 10 HYDRAULIC STORAGE: Minimum 50 gal. bulk hydraulic storage tank, mounted YES NO	3	ENGINE:		
4 TRANSMISSION: Full automatic shift with selectable drive modes. Minimum 10 forward speeds. 5 DRIVE AXLES: Must be selectable 4 wheel drive. Automatic locking differential in rear axle. 6 BRAKES: Service brakes shall be all hydraulic, power operated, antilock at both axles. 7 TIRES: All tires shall be a minimum of 225/70R19.5. 8 AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose yes no compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. 10 HYDRAULIC STORAGE: Minimum 50 gal. bulk hydraulic storage tank, mounted YES NO			VES	NO I
Full automatic shift with selectable drive modes. Minimum 10 forward speeds. 5 DRIVE AXLES: Must be selectable 4 wheel drive. Automatic locking differential in rear axle. 6 BRAKES: Service brakes shall be all hydraulic, power operated, antilock at both axles. 7 TIRES: All tires shall be a minimum of 225/70R19.5. 8 AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. 10 HYDRAULIC STORAGE: Minimum 50 gal. bulk hydraulic storage tank, mounted YES NO		Casoline vo engine.	120	110
Full automatic shift with selectable drive modes. Minimum 10 forward speeds. 5 DRIVE AXLES: Must be selectable 4 wheel drive. Automatic locking differential in rear axle. 6 BRAKES: Service brakes shall be all hydraulic, power operated, antilock at both axles. 7 TIRES: All tires shall be a minimum of 225/70R19.5. 8 AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. 10 HYDRAULIC STORAGE: Minimum 50 gal. bulk hydraulic storage tank, mounted YES NO	1	TD ANGMICCION:		1
modes. Minimum 10 forward speeds. 5 DRIVE AXLES: Must be selectable 4 wheel drive. Automatic locking differential in rear axle. 6 BRAKES: Service brakes shall be all hydraulic, power operated, antilock at both axles. 7 TIRES: All tires shall be a minimum of 225/70R19.5. 8 AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. 9 LIFT GATE: Self contained hydraulic lift gate with minimum 1,200 YES NO Ibs capacity and treadplate platform.	4		VE0	NO
5 DRIVE AXLES: Must be selectable 4 wheel drive. Automatic locking differential in rear axle. 6 BRAKES: Service brakes shall be all hydraulic, power operated, antilock at both axles. 7 TIRES: All tires shall be a minimum of 225/70R19.5. 8 AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. 9 LIFT GATE: Self contained hydraulic lift gate with minimum 1,200 YES NO Ibs capacity and treadplate platform.			YES	NO
Must be selectable 4 wheel drive. Automatic locking differential in rear axle. BRAKES: Service brakes shall be all hydraulic, power operated, antilock at both axles. 7 TIRES: All tires shall be a minimum of 225/70R19.5. 8 AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. YES NO 9 LIFT GATE: Self contained hydraulic lift gate with minimum 1,200 YES NO Ibs capacity and treadplate platform.		modes. Minimum 10 forward speeds.		
Must be selectable 4 wheel drive. Automatic locking differential in rear axle. BRAKES: Service brakes shall be all hydraulic, power operated, antilock at both axles. 7 TIRES: All tires shall be a minimum of 225/70R19.5. 8 AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. YES NO 9 LIFT GATE: Self contained hydraulic lift gate with minimum 1,200 YES NO Ibs capacity and treadplate platform.				
Automatic locking differential in rear axle. Automatic locking differential in rear axle. BRAKES: Service brakes shall be all hydraulic, power operated, antilock at both axles. 7 TIRES: All tires shall be a minimum of 225/70R19.5. 8 AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose YES NO compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. YES NO 9 LIFT GATE: Self contained hydraulic lift gate with minimum 1,200 YES NO lbs capacity and treadplate platform.	5			
6 BRAKES: Service brakes shall be all hydraulic, power operated, antilock at both axles. 7 TIRES: All tires shall be a minimum of 225/70R19.5. 8 AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose YES NO compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. 9 LIFT GATE: Self contained hydraulic lift gate with minimum 1,200 YES NO lbs capacity and treadplate platform.		Must be selectable 4 wheel drive.	YES	NO
6 BRAKES: Service brakes shall be all hydraulic, power operated, antilock at both axles. 7 TIRES: All tires shall be a minimum of 225/70R19.5. 8 AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose YES NO compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. 9 LIFT GATE: Self contained hydraulic lift gate with minimum 1,200 YES NO lbs capacity and treadplate platform.				
6 BRAKES: Service brakes shall be all hydraulic, power operated, antilock at both axles. 7 TIRES: All tires shall be a minimum of 225/70R19.5. 8 AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose YES NO compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. 9 LIFT GATE: Self contained hydraulic lift gate with minimum 1,200 YES NO lbs capacity and treadplate platform.		Automatic locking differential in rear axle.	YES	NO
Service brakes shall be all hydraulic, power operated, antilock at both axles. 7 TIRES: All tires shall be a minimum of 225/70R19.5. 8 AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose yes NO compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. 9 LIFT GATE: Self contained hydraulic lift gate with minimum 1,200 yes NO lbs capacity and treadplate platform.		gg		
Service brakes shall be all hydraulic, power operated, antilock at both axles. 7 TIRES: All tires shall be a minimum of 225/70R19.5. 8 AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose yes NO compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. 9 LIFT GATE: Self contained hydraulic lift gate with minimum 1,200 yes NO lbs capacity and treadplate platform.	6	BRAKES:		
operated, antilock at both axles. 7 TIRES: All tires shall be a minimum of 225/70R19.5. 8 AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose yes NO compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. 9 LIFT GATE: Self contained hydraulic lift gate with minimum 1,200 yes NO lbs capacity and treadplate platform. 10 HYDRAULIC STORAGE: Minimum 50 gal. bulk hydraulic storage tank, mounted yes NO	"		VEQ	NO
7 TIRES: All tires shall be a minimum of 225/70R19.5. 8 AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose YES NO compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. 9 LIFT GATE: Self contained hydraulic lift gate with minimum 1,200 YES NO lbs capacity and treadplate platform.			ILO	NO
All tires shall be a minimum of 225/70R19.5. AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose YES NO compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. YES NO PLIFT GATE: Self contained hydraulic lift gate with minimum 1,200 YES NO lbs capacity and treadplate platform.		operated, antilock at both axies.		
All tires shall be a minimum of 225/70R19.5. AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose YES NO compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. YES NO PLIFT GATE: Self contained hydraulic lift gate with minimum 1,200 YES NO lbs capacity and treadplate platform.		TIDEO.		
8 AIR COMPRESSOR: Compressor shall be equipped with a multi-purpose YES NO compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. YES NO 9 LIFT GATE: Self contained hydraulic lift gate with minimum 1,200 YES NO lbs capacity and treadplate platform.	'		VE0	NO
Compressor shall be equipped with a multi-purpose compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. YES NO PLIFT GATE: Self contained hydraulic lift gate with minimum 1,200 YES NO lbs capacity and treadplate platform.		All tires shall be a minimum of 225/70R19.5.	YES	NO
Compressor shall be equipped with a multi-purpose compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. YES NO PLIFT GATE: Self contained hydraulic lift gate with minimum 1,200 YES NO lbs capacity and treadplate platform.				
compressor, 12/24 volt jump starter, welder, generator, PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. YES NO 9 LIFT GATE: Self contained hydraulic lift gate with minimum 1,200 YES NO lbs capacity and treadplate platform. 10 HYDRAULIC STORAGE: Minimum 50 gal. bulk hydraulic storage tank, mounted YES NO	8			
PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. YES NO PIFT GATE: Self contained hydraulic lift gate with minimum 1,200 YES NO lbs capacity and treadplate platform. PTO driven, with a bed mounted hydraulic tank, Control panel remote mounted hydraulic storage tank, mounted		Compressor shall be equipped with a multi-purpose	YES	NO
Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. YES NO PLIFT GATE: Self contained hydraulic lift gate with minimum 1,200 YES NO lbs capacity and treadplate platform. NO HYDRAULIC STORAGE: Minimum 50 gal. bulk hydraulic storage tank, mounted YES NO		compressor, 12/24 volt jump starter, welder, generator,		
Control panel remote mounted in road side compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. YES NO PLIFT GATE: Self contained hydraulic lift gate with minimum 1,200 YES NO lbs capacity and treadplate platform. NO HYDRAULIC STORAGE: Minimum 50 gal. bulk hydraulic storage tank, mounted YES NO		PTO driven, with a bed mounted hydraulic tank,		
compartment. 50 ft. air hose mounted on curb side with retractable reel. Minimum 150 psi air pressure. YES NO PLIFT GATE: Self contained hydraulic lift gate with minimum 1,200 YES NO lbs capacity and treadplate platform. HYDRAULIC STORAGE: Minimum 50 gal. bulk hydraulic storage tank, mounted YES NO		-		
side with retractable reel. Minimum 150 psi air pressure. 9 LIFT GATE: Self contained hydraulic lift gate with minimum 1,200 YES NO lbs capacity and treadplate platform. 10 HYDRAULIC STORAGE: Minimum 50 gal. bulk hydraulic storage tank, mounted YES NO				
Minimum 150 psi air pressure. 9 LIFT GATE: Self contained hydraulic lift gate with minimum 1,200 YES NO lbs capacity and treadplate platform. 10 HYDRAULIC STORAGE: Minimum 50 gal. bulk hydraulic storage tank, mounted YES NO		·		
9 LIFT GATE: Self contained hydraulic lift gate with minimum 1,200 YES NO lbs capacity and treadplate platform. 10 HYDRAULIC STORAGE: Minimum 50 gal. bulk hydraulic storage tank, mounted YES NO		SING WILLI TELLAGIADIG TEGI.		
9 LIFT GATE: Self contained hydraulic lift gate with minimum 1,200 YES NO lbs capacity and treadplate platform. 10 HYDRAULIC STORAGE: Minimum 50 gal. bulk hydraulic storage tank, mounted YES NO		Minimum 450 noi air progrum	VEC	NO
Self contained hydraulic lift gate with minimum 1,200 YES NO lbs capacity and treadplate platform. 10 HYDRAULIC STORAGE: Minimum 50 gal. bulk hydraulic storage tank, mounted YES NO		willimum 150 psi ali pressure.	1 = 0	INU
Self contained hydraulic lift gate with minimum 1,200 YES NO lbs capacity and treadplate platform. 10 HYDRAULIC STORAGE: Minimum 50 gal. bulk hydraulic storage tank, mounted YES NO		LIFTOATE		
lbs capacity and treadplate platform. 10 HYDRAULIC STORAGE: Minimum 50 gal. bulk hydraulic storage tank, mounted YES NO	⁹			
10 HYDRAULIC STORAGE: Minimum 50 gal. bulk hydraulic storage tank, mounted YES NO		· · · · · · · · · · · · · · · · · · ·	YES	NO
Minimum 50 gal. bulk hydraulic storage tank, mounted YES NO		lbs capacity and treadplate platform.		
Minimum 50 gal. bulk hydraulic storage tank, mounted YES NO				
	10	HYDRAULIC STORAGE:		
		Minimum 50 gal. bulk hydraulic storage tank, mounted	YES	NO
		in bed with 50 ft. retractable hose reel and dispenser.		

11 FUEL STORAGE: Minimum 50 gal. bulk fuel storage tank, mounted in bed with 50 ft. retractable hose reel and auto shut off filtered dispenser.	YES	NO
Gas bottle storage with tank holders for torch.	YES	NO
12 ELECTRICAL: Two 12 volt batteries shall have a minimum capacity rating of 800 cca. Dual alternators shall be a minimum of 320 total amps. Unit shall have a minimum of 2 front and 2 rear adjustable work lights.	YES	NO
Unit shall have a maximum 192 in. wheelbase, extended cab with rear seat access doors. Power windows and locks, power heated outside tow mirrors. Manual control for air conditioner, defrost, heat, washers/wipers, dome light. Tinted safety glass, rubber floor covering. Operators seats shall be fabric, type that is adjustable for operator height, leg reach, and back angle preference.	YES	NO
14 CAB INSTRUMENTATION: Cab instrumentation shall include dash mounted gauges and/or monitor system to include: transmission oil temp., transmission oil pressure, fuel, engine coolant temp., engine oil pressure, electric hours meter, electric voltage and engine RPM. Engine coolant and engine pressure systems shall include visual warnings.	YES	NO
15 ADDITIONAL EQUIPMENT: Unit shall be equipped with all standard equipment and shall include: bed mounted tire storage for 22.5 tires, compartment drawers for tools on curb side, ac/dc power supply, 2.5 in. towing receiver, 7 way RV electrical connector, rear view camera, cargo tie down rings mounted in bed, torch storage hooks, white exterior paint to include service body.	YES	NO
16 WARRANTY: Manufacturer's warranty shall be a minimum of 36 months on truck with minimum 60,000 miles on powertrain. Bidder shall attach a copy of warranty.	YES	NO
17 EXTENDED COVERAGE CONTRACT: In addition to manufacturer's warranty, bidder shall	YES	NO

offer an extended coverage contract for equpiment repair, parts and labor, for a minimum of 36 months or 36,000 miles, Bidder shall attach copy of proposed extended coverage contract.

18 REPAIR PARTS AND SERVICE:

Since the continuous operation of this truck is of the utmost importance, sometimes of emergency nature, it is necessary that the successful bidder be in a position to render prompt parts and service. The successful bidder shall maintain and/or have access to parts inventory within fifty (50) miles. Said parts inventory shall be sufficient size and variety to offer a level of parts availability of ninety-five (95%) within forty-eight (48) hours from time of order by the customer. availability of normal order by the customer. Availability of normal order by the customer. Availability of normal maintenance items such as filters, V-belts, hydraulic lines, and hoses shall not exceed twenty-four (24) hours. Bidder shall attach his proposed program for parts and service availability for evaluation. Review of the bidder's ability to provide prompt parts and service will be used in determining low qualified bidder. If equipment repair cannot be made within forty-eight (48) hours the successful bidder will supply the Street Department with the same or equal equipment for the period of the repair. The successful bidder has been a provider and service handler of this type of equipment for a minimum of ten (10) continuous years.

YES NO

19 MANUALS:

Successful bidders shall provide a copy of the operators manuals.

YES N

NO


20 MANUFACTURING:

What percentage of this truck is manufactured in the United States.

%

21 **DELIVERY TIME**:

How long to have truck delivered?



FINANCE & ACCOUNTING

Funding Verification/Encumbrance Request Form

Date to be submitted to BoW/Park Board: 7/25/24		(put N/A if not subn	nitting to BoW/Park Board)
Vendor name: Don Hinds			
Vendor Address: 12610 Ford Drive, Fishers	s, IN	46038	
Brief description of purchase: Shop Service Tru			
	Fund	1#	290
Source of Funding:	Department #		025
Current Year Operational Budget Subsequent Year Operational Budget ¹	Project # (NA if no project #)		n/a
Funding not yet finalized (attach explanation) ²	44	Expense Object #	Amount
Loan or debt proceeds	#1	451.100	\$ 105,562.00
Non-Appropriated Fund ³ 1) This option may only be selected AFTER the adaption of the subse	#3		
Are you requesting that a Purchase Order (PO) be created for all purchases/contracts that will not not select for all purchases/contracts that will not not select ONLY if department plans to initiate possible that sufficient appropriation authority.	<u>ot</u> be pe ayment	ald immediately immediately	expense series to obligate the
epartment Director	_	Note: Tolkings	0107104
Signature)		Patty Johnson Inted Name)	6/27/24 (Date)
lease email completed form to OF <u>Abudget@noblesvil.6.in</u> go	•	mieu namej	(sector)
OR OFFICE OF FINANCE AND ACCOUNTING USE ONLY			
OFA Action Taken Purchase Order Created Reviewed Availability of funds (Contract/Purchase of Contract/Purchase o		- Anna Anna Anna Anna Anna Anna Anna Ann	
	is form i	n purchase/contract approve	al submission)
Comments: Initials: Date: 1111	is form i	n purchase/contract approve	al submission)